

SUNISO 5GS REFRIGERATION OIL

ENGINEERING CONTROLS: Local exhaust ventilation recommended.

PERSONAL PROTECTION: Use gloves to prevent prolonged skin contact.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE:	Negligible	VAPOR DENSITY (Air=1):	>5
SPECIFIC GRAVITY:	0.9	EVAPORATION RATE (N-BUTYL ACETATE=1):	>1
SOLUBILITY IN WATER:	Insoluble	VOC (G/L):	0
pH:	NA	FREEZING POINT:	
BOILING POINT:	260 C		
APPEARANCE & ODOR:	Light golden liquid, oil odor		

SECTION X - STABILITY AND REACTIVITY

STABILITY: Stable.
CONDITIONS TO AVOID: Ignition sources.
MATERIALS TO AVOID: Oxidizers.
HAZARDOUS DECOMPOSITION PRODUCTS: Combustion: Smoke, carbon monoxide, carbon dioxide.
HAZARDOUS POLYMERIZATION: Will not occur.

SECTION XI - TOXICOLOGICAL INFORMATION

Mineral oil LD50: 402 g/kg (skin: mouse)

SECTION XII - ECOLOGICAL INFORMATION

Not available.

SECTION XIII - DISPOSAL CONSIDERATIONS

Dispose as hazardous waste. Classification and documentation is required before disposal. Follow all local, state and federal regulations.

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Not regulated material, liquid

HAZARD CLASS: NA
IDENTIFICATION NUMBER: NA
DOT Emergency Guide #: NA
Reportable Quantity (RQ): NA
International: NA

SECTION XV - REGULATORY INFORMATION

TSCA (Toxic Substance Control Act): Components of this product are listed on the TSCA Inventory.
CERCLA (Comprehensive Environmental Response, Compensation and Liability Act): Not listed.

SARA TITLE III (Superfund Amendments and Reauthorization Act): None listed.

CALIFORNIA PROPOSITION 65: WARNING: This product contains mineral oils, a chemical known to the State of California to cause cancer.

SECTION XVI - OTHER INFORMATION

State Right-to-Know Programs: None

NFPA Ratings
Health: 0
Flammability: 1
Reactivity: 0
HMIS Protective Equipment: X See your supervisor
Revised 10/2001